

# PP 2-32 / 65

## PNEUMATIC DOVETAIL ROUTING MACHINE



Free-standing version with solid cast table and large working surface at a comfortable working height.

With two stations comprising of twin spindle routers at a fixed spacing. Choice of 32 mm or 65 mm cross centres, options of alternative cross-centres. Routing two dovetail slots in each work-piece with each machine cycle Hoffmann Key sizes W-1/2/3. Option W-4.

Other spindle spacing available.

### Technical data

	PP 2-32	PP 2-65
Electrical	3ph/N/PE 230/400 V 50/60Hz 4.0 kW	1ph/N/PE 230 V 50/60Hz 2.2 kW
Pneumatic	6 bar	6 bar
Motors	1 x 1000 W	1 x 530 W
Motor speed	34.000 1/min.	29.000 1/min.
Control	pneumatisch	pneumatisch
Clamping	pneumatisch	pneumatisch
Work-piece height	150 mm	150 mm
Router depth	0-115 mm	0-115 mm
Extraction port	Ø 100 mm	Ø 100 mm
Hoffmann Key sizes	W 1 / 2 / 3 / (4 optional)	W 1 / 2 / 3 (4 optional)
Dimensions W/D/H	1000 / 750 / 1500 mm	1000 / 750 / 1500 mm
Weight	225 kg	160 kg
Order No.	W 108 2000	W 108 1000

Technical changes without notice.



### Hoffmann GmbH Maschinenbau

Mergelgrube 5 · 76646 Bruchsal (Germany)  
Phone +49 7251 9544-0 · Fax +49 7251 9544-44  
info@hoffmann-schwalbe.de · www.hoffmann-schwalbe.de

