

PU 2-32 / 65


PNEUMATIC DOVETAIL ROUTING MACHINE



Free-standing version with solid cast table and large working surface at a comfortable working height. With a single station comprising of twin spindle routers at a fixed spacing. Choice of 32mm or 65mm cross centres (options of alternative cross-centres). Routing two dovetail slots with each machine cycle Hoffmann Key sizes W-1/2/3. Option W-4.

Function

The automatic machine cycle is started by pressing the foot-pedal. The positioned work-piece is clamped and the routed vertically to the pre-set depth. The unit returns to its home position and the work-piece is released. The motor switches on and off automatically. Adjustment of the fences and router depths is made manually.



Router units with spindle spacing 65 mm

Technical data

	PU 2-32	PU 2-65
Electrical	1ph/N/PE 230 V 50/60Hz 1,0 kW	1ph/N/PE 230 V 50/60Hz 1,1kW
Pneumatic	6 bar	6 bar
Motors	1 x 1000 W	1 x 530 W
Motor speed	34.000 1/min.	29.000 1/min.
Control	pneumatisch	pneumatisch
Clamping	pneumatisch	pneumatisch
Work-piece height	150 mm	150 mm
Router depth	0-115 mm	0-115 mm
Extraction port	Ø 100 mm	Ø 100 mm
Hoffmann Key sizes	W 1 / 2 / 3	W 1 / 2 / 3
Dimensions W/D/H	820 / 700 / 1500 mm	820 / 700 / 1500 mm
Weight	130 kg	130 kg
Order No.	W 107 3000	W 107 2000

Technical changes without notice.



Hoffmann GmbH Maschinenbau

Mergelgrube 5 · 76646 Bruchsal (Germany)
Phone +49 7251 9544-0 · Fax +49 7251 9544-44
info@hoffmann-schwalbe.de · www.hoffmann-schwalbe.de

