

PU 2

PNEUMATIC DOVETAIL ROUTING MACHINE



Free-standing version with solid cast table and large working surface at a comfortable working height. With a single router unit which routs a single dovetail slot with each machine cycle for Hoffmann Key sizes W-1/2/3/4.

Function

The automatic machine cycle is started by pressing the foot-pedal. The positioned workpiece is clamped and the routed vertically to the pre-set depth. The unit returns to its home position and the work-piece is released. The motor switches on and off automatically. Adjustment of the fences and router depths is made manually.



1. Work-piece clamping
2. Router depth setting
3. Centre fence plate 45°
4. But-stop

Technical data

Electrical	1ph/N/PE 230 V 50/60Hz 1,0 kW
Pneumatic	6 bar
Motor	1 x 1000 W
Motor speed	34.000 1/min.
Control	pneumatisch
Clamping	pneumatisch
Work-piece height	150 mm
Router depth	0-115 mm
Extraction port	Ø 100 mm
Hoffmann Key sizes	W 1 / 2 / 3 / 4
Dimensions W/D/H	800 / 750 / 1500 mm
Weight	119 kg
Order No.	W 107 0000

Technical changes without notice.



Hoffmann GmbH Maschinenbau

Mergelgrube 5 · 76646 Bruchsal (Germany)
Phone +49 7251 9544-0 · Fax +49 7251 9544-44
info@hoffmann-schwalbe.de · www.hoffmann-schwalbe.de

