

...the Hoffmann Dovetail Key


MU 3 / MU 3-D Manual Dovetail Routing Machine











Operation

Position and secure the fence plate and lay the work-piece against it. By drawing down the hand lever, the workpiece is clamped and the motor starts. Continued pressure on the lever raises the router unit through the workpiece and to the pre-set routing depth. When the hand lever is returned to its original position motor switches off automatically and the routed work-piece is released.


On the model version MU 3-D the routing position, as well as the routing depth are digitally displayed to an accuracy of 1/10th mm.



Options



Digital display for:







Fine motor adjustment



Fences

Angle fence



Butt stop fence



Internal fence



Angle fence plate elevation



Butt stop fence elevation



Internal fence elevation










Cornice fence



Adjustable internal fence



Adjustable fence "Synchro" 0-90°







Technical data

recilificat data		
Electrical connection	1ph/N/PE 230 V 50/60Hz 1.0 kW	
Motor	1 x 1000 W	
Rotation speed without load	34000 1/min.	
Control	manual	
Work-piece clamping	manual	
Height capacity	130 mm	
Routing depth	0-85 mm	
Extraction port size	Ø 50 mm	
Hoffmann Key sizes	W-0/1/2/3/4	
Overall sizes B/W/H	740/650/835	
Weight	32 kg	
Order No.	W1031000	



...brilliantly simple

Scale with magnifying lense

Routing depth

and lever limiter

Ergonomic lever design



Ergonomic operator bay

Centre line location jig

MU 3-P / MU 3-PD Pneumatic Dovetail Routing Machine



Transportable and adaptable bench-top machine, to rout a single dovetail slot with each machine cycle for Hoffmann Keys sizes W-0/-1/-2/-3 /-4.

Operation

Position and secure the fence plate and lay the work-piece against it. By actuating the foot pedal, the work-piece is pneumatically clamped and the motor starts. The router unit rises through the work-piece and to the pre-set routing depth. When the routing depth is reached the unit returns to its home position and switches off. The routed workpiece is then released.



Electrical connection 1ph/N/PE 230 V 50/60Hz 1.0 kW Air pressure 6 bar Motor 1 x 1000 W Rotation speed without load 34000 1/min. Control pneumatic Work-piece clamping pneumatic Height capacity 150 mm Routing depth 0-95 mm Extraction port size Ø 50 mm Hoffmann Key sizes W-0/1/2/3/4 Overall sizes B/W/H 740/650/835 Weight 32 kg Order No. W1032000

Machines & Accessories

MU 3 / MU 3-P

Machines

MU 3 Dovetail routing machine manual	W1031000	MU 3-P Dovetail routing machine pneumatic	W1032000

Accessories

W3060000
W3010000
W3012000
W3011000
W3013000
W3014000
W3015000
W3016000
W3017000
W3018000
W3019000

Butt stop fence	W3020000
Cornice fence	W3021000
Flip stop for extension fence	W3022000
Flip stop for rear fence plane	W3023000
Flip stop "Mini"	W3024000
Centre line location jig	W3025000
Multi digital gauge	W3026000
Laser line	W3027000
Routing depth and lever limiter	W3028000
Extension fence, 1000 mm each	W3029000
Mullion fence guide	W3030000
Sliding fence	W3031000



Hoffmann GmbH Maschinenbau

Mergelgrube 5 · D-76646 Bruchsal

Telefon +49 (0) 72 51 - 95 44 0 Telefax +49 (0) 72 51 - 95 44 44 www.hoffmann-schwalbe.de Home info@hoffmann-schwalbe.de E-Mail

Were found in the

best joints...worldwide!